



LED DISPLAYS:ELS-23101A/B SERIES

ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta=25℃)

Part No.	Emitted Color	Peak Wave Length	Epoxy Color	Surface Color	Common Electrode	$\Delta\lambda$ (nm)	If (mA)	Peak (mA)	Vf(V)		IV(mcd)	
									Segment	Dot	Min	Max
ELS-23101AS	Red	620-630	White	Black	Cathode	10	20	60	7.2-8.0	3.6-4.0	82	92
ELS-23101AO	Orange	600-610	White	Black	Cathode	10	20	60	7.2-8.0	3.6-4.0	85	95
ELS-23101AY	Yellow	585-595	White	Black	Cathode	10	20	60	7.2-8.0	3.6-4.0	88	98
ELS-23101AG	Olivine	565-575	White	Black	Cathode	10	20	60	7.2-8.0	3.6-4.0	10	20
ELS-23101AGG	Emerald	515-525	White	Black	Cathode	10	20	60	10.4-11.2	5.2-5.6	215	225
ELS-23101AB	Blue	460-470	White	Black	Cathode	10	20	60	10.4-11.2	5.2-5.6	15	25
ELS-23101AW	White	-	-	Black	Cathode	-	20	60	10.4-11.2	5.2-5.6	-	-
ELS-23101BS	Red	620-630	White	Black	Anode	10	20	60	7.2-8.0	3.6-4.0	82	92
ELS-23101BO	Orange	600-610	White	Black	Anode	10	20	60	7.2-8.0	3.6-4.0	85	95
ELS-23101BY	Yellow	585-595	White	Black	Anode	10	20	60	7.2-8.0	3.6-4.0	88	98
ELS-23101BG	Olivine	565-575	White	Black	Anode	10	20	60	7.2-8.0	3.6-4.0	10	20
ELS-23101BGG	Emerald	515-525	White	Black	Anode	10	20	60	10.4-11.2	5.2-5.6	215	225
ELS-23101BB	Blue	460-470	White	Black	Anode	10	20	60	10.4-11.2	5.2-5.6	15	25
ELS-23101BW	White	-	-	Black	Anode	-	20	60	10.4-11.2	5.2-5.6	-	-

ABSOLUTE MAXIMUM RATINGS (Ta=25℃)

Reverse Voltage	Reverse Current (V _R =5V)	Operating Temperature Range	Storage Temperature Range	Lead Soldering Temperature
5V	20 μ A	-20℃~+80℃	-30℃~+80℃	255 ℃ For 3 seconds

PACKAGE DIMENSION (Unit: millimeters, Tolerance : ±0.25mm)

