



LED DISPLAYS:ELA-0801 SERIES

ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta=25℃)

Part No.	Emitted Color	Peak Wave Length	Epoxy Color	Surface Color	$\Delta\lambda$ (nm)	Pd (mW)	If (mA)	Peak (mA)	Vf(V)		IV(mcd)	
									Min	Max	Min	Max
ELA-0801S	Red	620-630	White	Black	10	35	20	60	7.2	8.0	82	92
ELA-0801O	Orange	600-610	White	Black	10	35	20	60	7.2	8.0	85	95
ELA-0801Y	Yellow	585-595	White	Black	10	35	20	60	7.2	8.0	88	98
ELA-0801G	Olivine	565-575	White	Black	10	35	20	60	7.2	8.0	10	20
ELA-0801GG	Emerald	515-525	White	Black	10	55	20	60	10.4	11.2	215	225
ELA-0801B	Blue	460-470	White	Black	10	55	20	60	10.4	11.2	15	25
ELA-0801W	White	-	-	Black	-	55	20	60	10.4	11.2	-	-

ABSOLUTE MAXIMUM RATINGS (Ta=25℃)

Reverse Voltage	Reverse Current (VR=5V)	Operating Temperature Range	Storage Temperature Range	Lead Soldering Temperature
5V	20 μ A	-20℃~+80℃	-30℃~+80℃	255 ℃ For 3 seconds

PACKAGE DIMENSION (Unit: millimeters, Tolerance : ± 0.25 mm)

